



TYPE	Push trolley PTM		1	2	3	5	10	-
TYPE	Gear trolley GTM		1	2	3	5	10	20
Capacity	T		1	2	3	5	10	20
Flange width B min.-max.		R2	64-203	88-203	100-203	114-203	124-203	136-203
		R3	64-305	88-305	100-305	114-305	124-305	136-305
Min. Curve radius	m		0.9	1	1.2	1.3	1.7	2.8
A (Dimensions)	mm		246	276	332	377	389	574
D	mm		68	80	100	110	136	175
E	mm		82	94	116	127	156	200
F	mm		125	150	171	196	285	315
G	mm		2	2	3	3	3	3
K	mm		38	38	40	42	22	30
N (RANGE - R2)	mm		311	327	343	355	403	-
N1 (RANGE - R2)	mm		338	349	362	374	480	537
N (RANGE - R3)	mm		-	-	-	430	450	-
N1 (RANGE - R3)	mm		-	-	-	480	500	-
Weight PTM	kg		10.5	17.5	27	41	48	-
Weight GTM	kg		14.5	21.5	31	46	95	244
Hand Chain Size	mm x pitch		5 x 25	5 x 25	5 x 25	5 x 25	5 x 25	5 x 25
Hand Chain		Blue Zinc Plated						
Trolley Wheel		Lining of HTB-2 on insert M.S./ En8 / En 9 / C.I.						

Data tolerance $\pm 10\%$