

Hoist Model	SWL Ton & Spectrum FEM Classification				Lifting Speed	Hoist Motor		Head Room	Rope Dia.	Reeving	Monorail Beam		Cross Travel			Typical GA Dimensions			Typical GA Dimensions			Typical GA Dimensions		
	4m	3m	2m	1Am		MPM	Type				kW	mm	mm	No. of Falls	Width Range mm	Thickness mm	Kw Two motors	MPM	mm	Lift 6 m			Lift 9 m	
																A	B	C	A	B	C	A	B	C
UR 1	2.00	2.50	3.2	N/A	1.0 / 6.3	Dual Speed	0.4 / 4.0	800	8	4	150-300	45	0.04 / 0.18	5 / 20	125	700	1240	700	700	1490	700	700	1740	700
UR 1i	2.00	2.50	3.2	N/A	6.3	Inverter Speed	4	800	8	4	150-300	45	0.18	20	125	700	1240	700	700	1490	700	700	1740	700
UR 2	2.80	4.40	5.5	6.8	0.8 / 5.0	Dual Speed	1.0 / 6.1	800	10	4	150-300	45	0.04 / 0.18	5 / 20	125	779	1461	721	779	1671	721	779	1850	721
UR 2i	2.80	4.40	5.5	6.8	5	Inverter Speed	6.1	800	10	4	150-300	45	0.18	20	125	779	1461	721	779	1671	721	779	1850	721
UR 3	6.30	8.00	10	12.5	0.8 / 5.0	Dual Speed	2.0 / 12.5	865	13	4	210-300	45	0.092 / 0.37	5 / 20	160	890	1461	830	890	1671	830	890	1881	830
UR 3i	6.30	8.00	10	12.5	5	Inverter Speed	12.5	865	13	4	210-300	45	0.37	20	160	890	1461	830	890	1671	830	890	1881	830
UR4	10.00	12.50	16	20	0.66 / 4.0	Dual Speed	2.6 / 16.0	1000	18	4	210-400	45	0.13 / 0.55	5 / 20	160	989	1700	931	989	1920	931	989	2130	931
UR 4i	10.00	12.50	16	20	4	Inverter Speed	16	1000	18	4	210-400	45	0.55	20	160	989	1700	931	989	1920	931	989	2130	931
UR5	12.50	16.00	20	25	0.53 / 3.4	Dual Speed	2.6 / 16.0	1600	18	4	210-400	45	0.13 / 0.55	5 / 20	160	970	2550	780	970	2850	780	970	3050	780
UR 5i	12.50	16.00	20	25	3.4	Inverter Speed	16	1600	18	4	210-400	45	0.55	20	160	970	2550	780	970	2850	780	970	3050	780
UR 6	20.00	25.00	32	40	0.65 / 2.63	Dual Speed	5.0 / 20	1800	22	4	210-400	45	0.18 / 0.75	5 / 20	160	1150	3200	1175	1150	3450	1175	1150	3700	1175

